Batch Controller



The 424 Batch Controller is suited to flow applications where precise measurement and control of batch quantities is required.

The 424 will interface to most flowmeters generating pulse or frequency outputs.



Features

- Displays Batch Total, Preset Quantity, Flow Rate, and Accumulated Total
- Software Control of Flow Input Type and Output Voltage
- Overrun Compensation
- Remote Operation
- No Flow Alarm
- Custom Headers for Ticket Printing
- Universal Mains Input Voltage
- Dual Relay Outputs
- Optional 4-20mA Outputs
- RS485 & R232 Output
- Adjustable Backlight
- Green, Red and Orange LED Status Lamps
- Tactile Keypad for Improved Operator Interaction


Specifications

Model Prefix	FRT
Displays	6 digits 17.8mm high LCD
Temperature Range	0°C to 55°C (32°F to 131°F
	(-20°C to +60 °C (-4°F to +140°F) with
	Conformal Coating)
Data Retention	All set up parameters and totals are stored in
	a non-volatile memory with 10 years
	retention.
Transducer Supply	8-24Vdc software adjustable, 50mA
	maximum
Power Requirements	DC Supply: 12-28.5Vdc 200mA typical
	current
	AC Supply: AC mains universal 100-240V
	input
Protection Class	IP65 (Nema 4X), ATEX, IECEx, CSA approved
	enclosures are available for hazardous areas
Frequency range	0Hz to 10kHz

Maximum Load	390 ohms from internal power, 950 ohms if externally powered	
Case	Aluminium	

Dimensions


Rear Panel




Overall dimensions:


- 144mm (5.7") width
- 72mm (2.9") height
- 179mm (7") depth

Enclosure Dimensions



Panel Cut Out





Product Codes

424	Batch Controller
-----	------------------

Enclosure Mounting

1	Panel Mounting
2	Field Mount Enclosure
3	Explosion Proof Enclosure

4-20mA Output

0	None
1	4-20mA Output

Power Supply

U	Universal 110/240Vac
D	12-28Vdc Supply

Special Options

N	No Option
С	Conformal Coating

Typical Part Number: 424.21UC

424 Batch Controller 20-

Filton Process Control Engineering
Unit 2, The Old Grain Store,
Ditchling Common Industrial Estate,
Ditchling, East Sussex
BN6 8SG
United Kingdom
Tel: 01444 248777

Fax: 01444 243750 Email: sales@filton.com